

## TEMPERATURE AND HUMIDITY CLIMATIC CHAMBER ACS UY 1200 VT

This climatic chamber performs temperature only or temperature and humidity test enclosure combined.

The limited variation in temperature and humidity within the test space is the accurate available today due to the state of the art.

The climate and temperature working ranges comply with all relevant testing standards such as DIN, ISO, MIL, IEC and ASTM.

The chamber has a Pc remote control.

### Suited for climatic testing:


- Electronics
- Automotive
- Military
- Aeronautics and aerospace
- Plastic and rubber materials

### CLIMATIC CHAMBER ACS UY 1200 VT

Temperature range	-30°C/+100°C
Thermal gradient	4m°C/min
Internal Dimension (WxDxH)	1000x995x1190 mm
Humidity control	available - from 10% to 95%



Fig. 1: Climatic chamber



## CENTROTECNICA S.r.l.

Headquarter and Test House: Via N. Sauro, 1 - 20068 Peschiera Borromeo (MI) - ITALY

Production Unit and Test House: Via Confalonieri, 23 - 20060 Masate (MI) - ITALY

Tel: +39 02 55305888 - Fax: +39 02 45503582

Email: [info@ctecnica.it](mailto:info@ctecnica.it) - Website: [www.centrotecnica.net](http://www.centrotecnica.net)